

DATASHEET

# Hitachi Advanced Server HA815 G3

Optimized for high performance and capacity, this AMD powered, 1U, dual-processor, rack server delivers a balance of compute and storage capacity with the flexibility to power a wide range of solutions and applications.

## The right fit for your Solutions

### Flexible High-Capacity Storage

The HA815 G3 supports up to ten (10) 2.5-inch drives with a maximum storage capacity of 153.6TB. To better match your requirements, we offer 300GB SAS 15K drives to the newest 15.36TB NVMe PM1733a drives. An additional 3.84TB can be added with the dual 1.92TB M.2 drive kit.

### I/O Expansion

Two Half-Height and Half-Length (HHHL) PCIe 5.0 slots along with two (2) OCP slots allow for plenty of options. An additional 480GB Boot Drive can be added without impacting the PCIe or OCP positions.

### Enterprise-Class Features

HA815 G3 provides the reliability, availability and serviceability (RAS) features demanded by business-critical enterprise applications. The server's modular design simplifies cable routing and reduces service time. Redundant, hot swappable drives and power supplies provide a resilient architecture for important applications, and Performance Fans are standard to ensure continuous operation during peak demand.

### Energy Efficiency

When replacing older or growing new infrastructure, the new HA8x5 G3 server line can reduce your energy footprint due to the higher core counts available per processor than the competition. Each 4th Gen AMD EPYC™ 96 core processor can replace two equivalent Intel processors when core count is the driving need, thereby reducing server count. AMD EPYC™ CPUs help minimize environmental impacts from data center operations while advancing your company's sustainability objectives.

### High Performance from the all new 4th Generation AMD EPYC™ Processors with up to 96 cores

From on-prem to cloud, for businesses of all sizes, AMD EPYC™ processor-powered solutions deliver breakthrough results regardless of your deployment model or workload type. Ask your Hitachi Vantara Sales professional about the AMD EPYC™ powered solution today.



TABLE 1: HITACHI ADVANCED SERVER HA815 G3

Specifications	
Processor	<ul style="list-style-type: none"> <li>One (1) or Two (2) 4th Gen AMD EPYC processors</li> <li>1MB L2/Core, Up to 32MB L3/CCD</li> <li>128 PCIe 5.0 Lanes</li> <li>64 IO Lanes support CXL1.1+ with bifurcations supported down to x4</li> </ul>
Form Factor	<ul style="list-style-type: none"> <li>1U</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>H x W x D (inch): 1.69 X 17.11 X 25.57</li> <li>H x W x D (cm): 4.29 X 43.46 X 64.94</li> </ul>
Chipset	<ul style="list-style-type: none"> <li>No chipset – System on Chip (SoC) design</li> </ul>
Storage	<ul style="list-style-type: none"> <li>Ten (10) 2.5" hot-plug NVMe SSDs</li> <li>Ten (10) 2.5" hot-plug SATA or SAS drives</li> <li>One 480GB NS204i-u Boot Drive</li> </ul>
Memory	<ul style="list-style-type: none"> <li>Total Slots: Twenty-four (24) DDR5 RDIMM slots, 12 Channels per processor, 1 DIMM per channel</li> <li>Capacity: Up to 6TB (24x256GB)</li> <li>Memory Type: 4800MT/s DDR5</li> <li>Memory Size: 32GB, 64GB, 96GB, 128GB and 256GB</li> </ul>
Expansion Slot	<ul style="list-style-type: none"> <li>Primary (Default) Riser- PCIe 5.0, Bus width X16, Connector width X16, HH/HL</li> <li>Secondary (optional) Riser- PCIe 5.0, Bus width X16, Connector width X16, Low Profile or Half-Height and Half-Length Slot</li> <li>Two (2) OCP 3.0 slots available</li> </ul>
Network Controller	<ul style="list-style-type: none"> <li>Dedicated 1 GbE management port</li> <li>Optional Network Interface Controller Add in Cards</li> </ul>
Front I/O	<ul style="list-style-type: none"> <li>Two (2) USB 3.2, One (1) Power Button and LED, Health LED, NIC status LED, Unit ID button/LED</li> </ul>
Storage Controller	<ul style="list-style-type: none"> <li>Multiple Smart Array Controllers supported up to SR932i-p x32 lanes 8GB Wide Cache, PCI</li> <li>RAID 1 supported on the NS204i-u boot optimized storage device</li> <li>Single NS204i-u kit supported</li> </ul>
Power Supply	<ul style="list-style-type: none"> <li>Redundant hot-plug Platinum 800W or 1600W AC PSU</li> <li>Redundant hot-plug Titanium 1000W or 1800-2200W AC PSU</li> </ul>
Cooling	<ul style="list-style-type: none"> <li>Seven (7) Performance fans</li> </ul>
Video	<ul style="list-style-type: none"> <li>Video modes up to 1920 x 1200@60Hz (32 bpp) and 16MB video memory</li> </ul>
System Management	<ul style="list-style-type: none"> <li>iLO 6 ASIC</li> </ul>
Rear I/O	<ul style="list-style-type: none"> <li>Two (2) USB 3.1, One (1) VGA, One (1) dedicated management port, Unit ID LED</li> </ul>

TABLE 1: CONTINUED

Specifications	
Operating Environment	<ul style="list-style-type: none"> <li>Operating temperature: 10° to 35°C (50° to 95°F) at sea level</li> <li>Non-operating temperature: -30° to 60°C (-22° to 140°F)</li> <li>Operating relative humidity: 8% to 90%RH.</li> <li>Non-operating relative humidity: 5% to 95%RH</li> </ul>
Security	<ul style="list-style-type: none"> <li>UEFI 2.9, UEFI Class 3 implementation, FIPS 140-3 validation, TPM (Trusted Platform Module) 2.0 option</li> </ul>
Weight (Max. Configuration)	<ul style="list-style-type: none"> <li>40KG</li> </ul>

**ABOUT HITACHI VANTARA**

Hitachi Vantara, a wholly-owned subsidiary of Hitachi Ltd., delivers the intelligent data platforms, infrastructure systems, and digital expertise that supports more than 80% of the Fortune 100. To learn how Hitachi Vantara turns businesses from data-rich to data-driven through agile digital processes, products, and experiences, visit [hitachivantara.com](https://hitachivantara.com).

**Learn More** →

Click here to read more about Hitachi Unified Compute Platform HC.



**Corporate Headquarters**  
 2535 Augustine Drive  
 Santa Clara, CA 95054 USA  
[hitachivantara.com](https://hitachivantara.com) | [community.hitachivantara.com](https://community.hitachivantara.com)

**Contact Information**  
 USA: 1-800-446-0744  
 Global: 1-858-547-4526  
[hitachivantara.com/contact](https://hitachivantara.com/contact)

© Hitachi Vantara LLC 2024. All Rights Reserved. HITACHI and Pentaho are trademarks or registered trademarks of Hitachi, Ltd. All other trademarks, service marks and company names are properties of their respective owners.

HV-BTD-DS-Hitachi-Advanced-Server-HA815-G3-13Feb24-A