Product Specification

## Hitachi Virtual Storage Platform 5000 Series Family Matrix

	5200	5200H	5600	5600H		
Performance (IOPS)	5.1M		33M			
Performance (Latency)	as low as 39µs					
Performance (Bandwidth)	52GB/s		312GB/s			
MAX. Raw Internal Capacity	23.1PB (30TB SSD)		69.3PB (30TB SSD)			
MAX. Raw External Capacity	287PB					
Data Availability	100% Guaranteed					
Data Reduction	Compression Accelerator Module					
Effective Capacity	4:1					
Data-at-Rest Encryption for NVMe and SAS	YES					
MAX. Number of Drives, Including Spares	33 NVMe SCM 96 NVMe 768 SFF SSD	33 NVMe SCM 96 NVMe 768 SFF SSD/HDD 384 LFF HDD	99 NVMe SCM 288 NVMe 2,304 SFF SSD	99 NVMe SCM 288 NVMe 2,304 SFF SSD/HDD 1,152 LFF HDD		
Drive Pack Upgrades (Sold in Packages of 4 Drives)	375GB NVMe SCM 60TB NVMe SSD 15TB NVMe SSD 7.6TB NVMe SSD 3.8TB NVMe SSD 1.9TB NVMe SSD 30TB SAS SSD 15TB SAS SSD 7.6TB SAS SSD 3.8TB SAS SSD 1.9TB SAS SSD	375GB NVMe SCM 60TB NVMe SSD 15TB NVMe SSD 7.6TB NVMe SSD 3.8TB NVMe SSD 1.9TB NVMe SSD 30TB SAS SSD 15TB SAS SSD 7.6TB SAS SSD 3.8TB SAS SSD 1.9TB SAS SSD 2.4TB 10K SAS HDD 14TB 7.2K SAS HDD 18TB 7.2K SAS HDD	375GB NVMe SCM 60TB NVMe SSD 15TB NVMe SSD 7.6TB NVMe SSD 3.8TB NVMe SSD 1.9TB NVMe SSD 30TB SAS SSD 15TB SAS SSD 7.6TB SAS SSD 3.8TB SAS SSD 1.9TB SAS SSD	375GB NVMe SCM 60TB NVMe SSD 15TB NVMe SSD 7.6TB NVMe SSD 3.8TB NVMe SSD 1.9TB NVMe SSD 30TB SAS SSD 15TB SAS SSD 7.6TB SAS SSD 3.8TB SAS SSD 1.9TB SAS SSD 2.4TB 10K SAS HDD 14TB 7.2K SAS HDD 18TB 7.2K SAS HDD		
Max. Flash Media Trays (Sold in Packages of 4)	4x NVMe SSD 32x SAS SSD		12x NVMe SSD 96x SAS SSD			
Max. HDD Media Trays (Sold in Packages of 8)	N/A	32x 10K SAS HDD 32x 7.2K SAS HDD	N/A	96x 10K SAS HDD 96x 7.2K SAS HDD		
No. Controller Blocks	1		1, 2 or 3			
Nodes Per System	2		2,4,6			
No. Controllers Per System	2		4,8,12			
Hitachi Accelerated Fabric	2x Node Interconnect Switch					
Controller Interconnectivity	4x Fabric Acceleration Modules 8, 16, 24x Fabric Acceleration Modules					
Node Dimensions: Height Width Depth	4U, 6.9" (174mm) 17.6" (446mm) 30.1" (763mm)					

## Hitachi Virtual Storage Platform 5000 Series Family Matrix

	5200	5200H	5600	5600H		
Host Interface Types	FC-NVMe: 32Gb/s FC: 16Gb/s FC: 32Gb/s IBM® FICON®: 16Gb/s					
	IBM® FICON®: 32Gb/s IBM® FICON® (with EDIF): 32Gb/s iSCSI: 10Gb/s					
MAX HOST Port Count	32×FC-NVMe 32×FC 32×FICON 16×iSCSI					
Max Fibre Bandwidth to Host	102.4GB/s		614.4GB/s			
Back-end Disk Interface and Links	32 x SAS or NVMe	32 x SAS or NVMe	192 x SAS and NVMe	192 x SAS and NVMe		
Max. Cache	1TiB		2TiB: 1x Controller Block 4TiB: 2x Controller Block 6TiB: 3x Controller Block			
RAID Supported	RAID-1* (2D+2D/4D+4D)  RAID-5 (3D+1P/7D+1P)  RAID-6 (6D+2P/14D+2P)					
MAX. LUN Size	256TB					
MAX. Number of LUNS	65,280					
MAX. Number of Snapshots	1,024 per LUN; 1,048,575 per system					
MAX. Number of Hosts per Fibre Channel Port	255					
Guarantees and SLAs	Cyber Resilience Guarantee					
	Sustainability SLA Guarantee Performance SLA Guarantee					
	100% Data Availability Guarantee					
	Effective Capacity Guarantee					
	Modern Storage Assurance					
Value Added Features	Storage Virtualization					
	In System Replication					
	Copy Management Infrastructure Analytics					
	Non-disruptive Migration					

<sup>\*</sup>RAID 1 selection mirrors blocks across two drives and then creates a striped set across multiple drive pairs. This is commonly referred to as RAID 1+0.

 $1TB = 1,000,000,000,000 \ \ \, \text{bytes} \qquad \text{LFF} = \text{large form factor} \qquad \text{NVMe} = \text{non-volatile memory express} \qquad \text{HDD} = \text{hard disk drive}$   $1TiB = 1,099,511,627,776 \ \ \, \text{bytes} \qquad \text{SCM} = \text{storage class memory} \qquad \text{SSD} = \text{solid state drive} \qquad \text{FC} = \text{Fibre Channel}$ 

SFF = small form factor SAS = serial attached SCSI FMD = flash module drive iSCSI = internet small computer systems interface

## Hitachi Vantara

Corporate Headquarters 2535 Augustine Drive Santa Clara, CA 95054 USA hitachivantara.com | community.hitachivantara.com Contact Information USA: 1-800-446-0744 Global: 1-858-547-4526 hitachivantara.com/contact