

DATASHEET

Hitachi Advanced Server HA810

Purpose built for excellent performance, high density and power efficiency, this general-purpose dual-processor server delivers a balance of compute and storage capacity with the flexibility to power a wide range of solutions and applications.



FLEXIBLE POWER FOR SOLUTIONS

High Performance

HA810 provides flexible memory and storage options to meet the needs of modern infrastructure solutions. The server provides Industry-leading Performance with Versatile Compute Via industry-standard technology leveraging the Intel Xeon Scalable processor with up to 28 cores, 12G SAS and 3.0 TB of 2933 MT/s DDR4 Memory.

High Capacity Storage

Achieve greater capacity with flexible drive configurations with up to 10 Small Form Factor (SFF) or with up to 4 Large Form Factor (LFF) drives delivering enhanced performance, capacity, and reliability to meet various customer segments and workload requirements at the right economics.

I/O Expansion

Full-height, low-profile and FlexibleLOM PCIe 3.0 expansion slots are available, as well as an AROC slot. In total the server supports up to 5 PCIe Gen3 expansion

slots. This allows the HA810 to be flexibly configured to optimize throughput, capacity and I/O performance for a wide range of enterprise applications.

Enterprise-Class Features

HA810 server provides the reliability, availability and serviceability (RAS) features demanded by business-critical enterprise applications. The server's modular design simplifies cable routing and reduces service time. Redundant, hot-swap drives, fans and power supplies provide a resilient architecture for important applications.

Embedded Server Management

An integrated baseboard management controller allows HA810 to be managed remotely and independently. A dedicated interface facilitates secure remote access through a LAN connection and provides a powerful, easy-to-use web console interface for remote initialization, management and configuration.

High Density and High Performance for Solution Workloads

With support of two Intel Xeon Scalable processors in just 1U rack space package, the Hitachi Advanced Server HA810 delivers exceptional compute density. It provides flexible memory and storage options to meet the needs of modern infrastructure solutions as well as dedicated application platforms such as Virtual Desktop infrastructure or and high performance applications in the data center.

The Intel Xeon Scalable processor family is optimized to address the growing demands on today's IT infrastructure. The server provides 24 slots for high-speed DDR4 memory, allowing up to 3TB memory capacity with LRDIMM population (128GB x 24) or 6TB (512GB x 12) with Intel Optane Persistent Memory population.

Learn More →

Converged and
Hyperconverged Infrastructure

HITACHI ADVANCED SERVER HA810

Processor	1st Gen Intel® Xeon® Scalable Processor Family / 2nd Gen Intel® Xeon® Scalable Processor Family Max. Thermal Design Power (TDP) Support: 205W Number of Processors: 2 processors Internal Interconnect: 9.6 or 10.4 giga transfers per second (GT/s)
Form Factor	1U
Dimensions	SFF: 4.29 x 43.46 x 70.7 cm / 1.69 x 17.11 x 27.83 in, LFF: 4.29 x 43.46 x 75.98 cm / 1.69 x 17.11 x 29.5 in
Weight(approximate)	SFF: Maximum: 16.3 kg (36 lbs), LFF: Maximum: 16.8 kg (37 lbs)
Chipset	Intel C621
Storage	SFF (2.5" SAS/SATA): standard: 8 or 10 max(optional): 11, LFF (3.5" SAS/SATA): standard 4
Memory	Total Slots: 24 Capacity / Memory type: (1st Gen) Up to 3TB (24 x 128GB DDR4 LRDIMMs@2666MT/s), Up to 768GB (24 x 32GB DDR4 RDIMMs@2666MT/s) (2nd Gen) Up to 6TB (12 x 512GB Intel Optane Persistent memory@2666MT/s), Up to 3TB (24 x 128GB DDR4 LRDIMMs@2933MT/s), Up to 1.5TB (24 x 64GB DDR4 RDIMMs@2933MT/s)
Expansion Slot	Standard Primary riser: PCIe Gen3 x8(full height, up to 9.5" length), x8(low profile, up to 9.5" length) (*) slot variation can be changed by optional riser
Network Controller	1 Flexible LOM slot available (Supporting a NICs adapter)
Other I/O Interfaces	(1) Serial port(optional), (2) Display port (1 rear VGA, 1 front (optional)), (1) USB 2.0(1 front (optional)), (5) USB 3.0 ports (1 front, 2 rear, 2 internal), (1) Front iLO Service Port, (1) Micro SD Slot
Storage Controller	Software RAID: Smart Array S100i controller. Essential RAID Controller: Smart Array E-series (optional) Performance RAID Controller: Smart Array P-series (optional)
Power Supply	(1+1) High-efficiency, redundant, hot-plug power supply unit (PSU) Platinum: 800W(100-240V ac), 1600W(200-240V ac)
Fan	(7) Standard fans, with fan redundancy (7) High performance fans(optional) with fan redundancy
Noise	Performance mode: Idle, less than 36 dBA, Operating, less than 45 dBA (*) Measured in accordance with ISO 7779. Acoustics levels will vary depending on system configuration.
Video	Integrated 1920 x 1200 DPI 60Hz(32bpp) with 16MB of video memory
System Management	iLo 5 - Monitor user's servers for ongoing management, service alerting, reporting and remote management with restful API UEFI Configure and boot user's servers securely with industry standard UEFI
Operating Environment	Operating temperature: 10°C to 35°C at sea level, with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight Altitude: Operating 3050m (10,000ft) Non-Operating 9144m (30,000ft) Operating relative humidity: 8% to 90%RH 28°C maximum wet bulb temperature, non-condensing Non-operating relative humidity: 5% to 95%RH 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing
Trusted Platform Module (TPM)	TPM 2.0 module

WE ARE HITACHI VANTARA

Hitachi Vantara solves digital challenges by guiding you from what's now to what's next. Our unmatched industrial and digital capabilities benefit both business and society.

Hitachi Vantara

Corporate Headquarters
2535 Augustine Drive
Santa Clara, CA 95054 USA
hitachivantara.com | community.hitachivantara.com

Contact Information
USA: 1-800-446-0744
Global: 1-858-547-4526
hitachivantara.com/contact

© Hitachi Vantara LLC 2022. All Rights Reserved. HITACHI and Lumada are trademarks or registered trademarks of Hitachi, Ltd. All other trademarks, service marks and company names are properties of their respective owners.

HV-CBE-DS-Hitachi Advanced Server HA810_24Aug22-A